# $\Xi \Pi \Xi X$

## FX BatmooZ





English



#### FEIMEX FX BatmooZ

The portable and battery-powered LED lamp is equipped with 4x 10W RGBW LEDs and with its lightweight design provides the ideal solution for optimum illumination without cable.

## FX BatmooZ



#### Portable, battery-powered LED lamp with IP65 motorized zoom


The FX BatmooZ is a portable, battery-powered LED-Light which can be applied without DMX- or Powercabeling. So your location is in perfect light within a few seconds and caluable construction time can be saved.

With the incredible motorized zoom with an angle between 8 ° and 40 ° several incredible effects and inserst can be made. This fact makes the FX BatmooZ unique.

A further highlight is the W-DMX-Receiver which makes it possible to use and control the FX BatmooZ without any cables. It is also possible to create your own personal scenes or use the dozens of colours stored in the internal library. These functions are making the battery-powered LED lamp the most flexible device on the market.

The FX BatmooZ can be customized in any surrounding. The standardcolour of the device is black but on correspondingly high quantity it is possible to order the LED-Light in white.

Thanks to the low power consumption of 50 W, the battery guarantees a runtime of up to 15 hours so you are never depend on cables anymore.



#### Design

The battery operated IP65 led lamp is available in black and white. The compact and lightweight design allows for versatile application.



#### Electronics & Features

Channels	6 Channels: Zoom, Setting, RGBW
	9 Channels: Strobe, Dimmer, Zoom,
	Setting, RGBW, CTO
	12 Channels: Strobe, Dimmer, Zoom,
	Setting, Colourmacro,
	RGBW, CTO, Auto, AT-SP
	Fade
W-DMX	Built with Wireless Solution- or
	LumenRadio-Receiver
Display	4 colour LCD-Display for auto- and
	userdefined programms,
	Master-/Slavemode

#### Structure and Power supply

Battery autonomy

Recharge time

7 hours of Full White (RGBW) 15 hours constant colour change





### Contact

FEIMEX GmbH Ottensener Strasse 8 22525 Hamburg Germany

T +49(0)40 468 991 790 F +49(0)40 468 991 7949 office@feimex.com www.feimex.com

## FX BatmooZ







Beam angle	8° to 40°
LED-Light Sources	
LEDs	4x Red, 4x Green, 4x Blue, 4x White
Colours	16,7 Million (R, G, B) 0 - 100 %
	saturation adjustable
Colour mixing	RGBW
Temperature ranges	
Operating temperature	- 20° C ~ + 40° C
Cooling	convection-cooled
Control & programming	
Protocol	DMX512 & W-DMX
Strobo	0 - 20 Hz
DMX-Channels	6, 9, 12 for advanced or basic controlling
Specifications	
Mains voltage	
Ivialitis vultaye	100V ~ 240V
Power consumption	100V ~ 240V 50W
Power consumption	50W
Power consumption DMX512-Connection	50W
Power consumption DMX512-Connection Housing	50W XLR 3p Input/Output injection-moulded aluminum and plastic
Power consumption DMX512-Connection <b>Housing</b> Material	50W XLR 3p Input/Output injection-moulded aluminum and plastic
Power consumption DMX512-Connection <b>Housing</b> Material	50W XLR 3p Input/Output injection-moulded aluminum and plastic black or wihite (requires correspondingly
Power consumption DMX512-Connection Housing Material Colour	50W XLR 3p Input/Output injection-moulded aluminum and plastic black or wihite (requires correspondingly high quantity)
Power consumption DMX512-Connection Housing Material Colour Protection class	50W XLR 3p Input/Output injection-moulded aluminum and plastic black or wihite (requires correspondingly high quantity)



